



KUBE II SCANNER

Lottery printers-Kube II Scanner

KUBE II SCANNER is the combination of a high performance scanner for cards and betting slips and a high speed thermal printer with stacker unit. KUBE II SCANNER works with standard lottery cards, 82 millimetre large and having a maximum length of 350 millimetres. It is capable of reading barcodes in combination with coupons and betting slips. The betting slips are printed on 80/82.5mm large paper, and the printer manages a paper roll with 150 mm diameter. The printed betting slips can be validated by printing the words "you won" or "validated" on them.

The one product for a complete solution!

- Scans cards
- Quickly prints betting slips
- Verifies and validates betting slips

Reads the barcode on the betting slip, checks its validity and validates the betting slip





















CHARACTERISTICS

- Embedded scanner
- Barcode reading
- Large paper roll
- Intelligent coupon scanning
- Branding feature to void ticket

EXCLUSIVE FEATURES

- Embedded scanner
- Barcode reading
- Large paper roll
- Intelligent coupon scanning
- Branding feature to void ticket
- Compact all-in-one unit
- 203 DPI printing resolution
- Memory expansion up to 2GB
- Mass Storage
- Windows and Linux drivers



• CardSet software tool to edit and modify your game slips (available for Windows)

SCANNER SPECIFICATIONS

- 203dpi resolution (8 dot/mm)
- Scanning speed: 250mm/sec
- Scanning Area: 82mm (W) x 350mm (L)
- Up to 40 programmable card types
- Data format: 256 shades of grey and b/w image, dot matrix (x,y)
- Rectangle search: 8800 max (total)
- Barcode reading
- CIS (Contact Image Sensor) technology
- Red scanning light (green optional)













APPLICATIONS

- Lotteries: odd reading, bet slip printing, winning slip recognition and/or validation
- Sports or horse racing betting: bet slip printing, reading or scanning, validation in case of wins, combined betting odds
- **Retail**: coupon reading and scanning, signed POS payment receipts, purchase data and loyalty points, discount deductions from the total bill
- Banks: cheque and banking document reading and scanning

TECHNICAL SHEET

Number of dots 8 dots / mm Resolution 203 dpi Printing (mm/sec) 190 Character set PC437, PC850, PC860, PC863, PC863, PC865, PC858 (euro) Printing Format Normal, height and width from 1x to 8x, expanded, reverse, underlined, script Printing Direction Straight, 90°, 180°, 270° Paper width 80mm/ 82.5mm Paper weight from 70 to 90 g/m² Roll Dimension max Ø 150mm Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Drivers Windows* 232/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) Tool software Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 6	Printing Method	Thermal printing
Printing (mm/sec) Character set PC437, PC850, PC860, PC863, PC858 (euro) Printing Format Normal, height and width from 1x to 8x, expanded, reverse, underlined, script Printing Direction Straight, 90°, 180°, 270° Paper width 80mm/ 82.5mm Paper weight from 70 to 90 g/m² Roll Dimension Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows* (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) Printer\$c, Custom PowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER (From FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EM0950 2001 Marks CE, RoHS Compliant Dimensions	Number of dots	8 dots / mm
Character set PC437, PC850, PC860, PC863, PC865, PC858 (euro) Printing Format Normal, height and width from 1x to 8x, expanded, reverse, underlined, script Printing Direction Straight, 90°, 180°, 270° Paper width 80mm/ 82.5mm Paper weight from 70 to 90 g/m² Roll Dimension max Ø 150mm Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Drivers Windows* (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER (From FW release 1.51 and higher) Power supply 24 Vdc ± 10% dexternal power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN6950 2001 Marks CE, ROHS Compliant Dimensions	Resolution	203 dpi
Printing Format Normal, height and width from 1x to 8x, expanded, reverse, underlined, script Printing Direction Straight, 90°, 180°, 270° Paper width 80mm/ 82.5mm Paper weight from 70 to 90 g/m² Roll Dimension max Ø 150mm Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows** (32/64 bit) — only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Printing (mm/sec)	190
Printing Direction Straight, 90°, 180°, 270° Paper width 80mm/ 82.5mm Paper weight from 70 to 90 g/m² Roll Dimension Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows* (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, ROHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Character set	PC437, PC850, PC860, PC863, PC865, PC858 (euro)
Paper width 80mm/ 82.5mm Paper weight from 70 to 90 g/m² Roll Dimension max Ø 150mm Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Printing Format	Normal, height and width from 1x to 8x, expanded, reverse, underlined, script
Paper weight from 70 to 90 g/m² Roll Dimension max Ø 150mm Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, Custom PowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER (from FW release 1.51 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Printing Direction	Straight, 90°, 180°, 270°
Roll Dimension max Ø 150mm Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Paper width	80mm/ 82.5mm
Emulation CUSTOM / POS Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (From FW release 1.45 and higher) KUBE II SCANNER (From FW release 1.51 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Paper weight	from 70 to 90 g/m²
Interfaces Serial (RJ45), USB, Ethernet interface Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (From FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, ROHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Roll Dimension	max Ø 150mm
Data Buffer 20 Kbytes Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) - only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER (From FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Emulation	CUSTOM / POS
Flash Memory 512 KB Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc±10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, ROHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Interfaces	Serial (RJ45), USB, Ethernet interface
Graphic Memory 2 logos with 608 x 862 dots Windows® (32/64 bit) - only on request WHQL and silent installation; Drivers Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) Tool software PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Data Buffer	20 Kbytes
Windows® (32/64 bit) – only on request WHQL and silent installation; Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, ROHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Flash Memory	512 KB
Drivers Linux (32/64 bit); Virtual COM (Linux or Windows 32/64 bit) Tool software PrinterSet, CustomPowerTool, CardSet Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Graphic Memory	2 logos with 608 x 862 dots
Tool software Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher) KUBE II SCANNER VERIPRINT (from FW release 1.51 and higher) Power supply 24 Vdc ± 10% (external power supply) Medium consumption 1 A on average (12.5% dots turned on) DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Drivers	Linux (32/64 bit);
Medium consumption1 A on average (12.5% dots turned on)DKD Function1 driver or customer display directly connectedMTBF60,600 hours (electronic board)SafetyEN60950 2001MarksCE, RoHS CompliantDimensions357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Tool software	Custom Windows API: KUBE II SCANNER (from FW release 1.45 and higher)
DKD Function 1 driver or customer display directly connected MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Power supply	24 Vdc ± 10% (external power supply)
MTBF 60,600 hours (electronic board) Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Medium consumption	1 A on average (12.5% dots turned on)
Safety EN60950 2001 Marks CE, RoHS Compliant Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	DKD Function	1 driver or customer display directly connected
Marks CE, RoHS Compliant 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	MTBF	60,600 hours (electronic board)
Dimensions 357(L) x 216(H) x 140(W)mm (with cover closed) 445(L) x 354(H) x 140(W)mm (with cover open)	Safety	EN60950 2001
445(L) x 354(H) x 140(W)mm (with cover open)	Marks	CE, RoHS Compliant
Weight 3.3 Kg	Dimensions	
	Weight	3.3 Kg










MODELS







911BS030200733 MULTIFUNCTION SYSTEM KUBEII SCANNER VERIPRINT

Via Berettine, 2 - 43010 Fontevivo PR - VAT: IT02498250345 - TEL: +39 0521 680111 - FAX: +39 0521 610701 - UNIQUE CODE: 8RQN7AZ

The technical data on this website are not binding and may be changed without advanced notice. Last update: 15 May 2024





